

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/095662 A1

(51) International Patent Classification⁷: **C22C 33/06**,
38/18, 38/24, 38/26, C23C 14/48

[GB/GB]; Loughborough University, Loughborough,
Leicestershire LE11 3TU (GB).

(21) International Application Number:
PCT/GB2005/001280

(74) Agent: **HARRISON GODDARD FOOTE**; 31 St.
Saviourgate, York YO1 8NQ (GB).

(22) International Filing Date: 1 April 2005 (01.04.2005)

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0407531.3 2 April 2004 (02.04.2004) GB

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,



(71) Applicant (*for all designated States except US*): **LOUGH-
BOROUGH UNIVERSITY** [GB/GB]; Loughborough,
Leicestershire LE11 3TU (GB).

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **FAULKNER, Roy**

[Continued on next page]

(54) Title: HIGH CHROMIUM FERRITIC STEEL WITH 0.5 ATOMIC % HAFNIUM, PART OF WHICH IS ION IMPLANTED



(57) Abstract: The application relates to the problem of improving the corrosion resistance and creep properties of standard Cr-steels like E911 (table 1) at high temperatures. To solve this problem, a method of adding up to 0.5 atomic % Hf both during casting or moulding and by ion implantation is provided. The addition of Hf improves the corrosion resistance and creep properties inter alia, as it forms a finely distributed stable second phase and as the harmful M23C6 disappears, because all carbon is taken by Hf to form HfC.



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*